

## PDR 922 HP [EL APDR 902]

Professional heat-pump dryer incl. powerful heat pump APDR 902

lowest energy consumption, without complicated exhaust ducting installation.



- Drum volume 400.00 l, load size 16.0 kg–22.0 kg
- Unique, gentle fabric care – honeycomb drum
- Automatic heat exchanger cleaning thanks to StreamClean process
- 60 % lower energy consumption than vented dryer\*
- Connected for the future using LAN and WiFi
- Fig. shows tumble dryer with heat pump module (order separately)

\* Heat pump dryers consume up to 60 % less energy than an electrically heated vented dryer.

EAN: 4002516409311 / Material number: 11718440 / Old Material Number: 52922021EU

| Construction type and version                         |                              |
|---|------------------------------|
| Construction type                                     | Front loader                 |
| Range   | Performance Plus             |
| Front   | Iron grey                    |
| Load size with a load ratio of 1:25                   | 16.0                         |
| Load size with a load ratio of 1:18                   | 22.0                         |
| Drum volume in l                                      | 400.00                       |
| Drying system   | Heat pump                    |
| Door opening [Ø] in mm                                | 520                          |
| Door opening angle in degrees                         | 180                          |
| Door hinge  | left                         |
| Convertible door hinging                              | •                            |
| Stainless steel honeycomb drum                        | Yes                          |
| Application   |                              |
| Suitable for the hotel and catering industry          | •                            |
| Suitable for retirement and care homes                | •                            |
| Suitable for facility management                      | •                            |
| Suitable for launderettes                             | •                            |
| Suitable for residential homes and apartments         | •                            |
| Suitable for dry cleaners                             | •                            |
| Suitable for commercial laundries                     | •                            |
| Suitable for fire brigades and rescue services        | •                            |
| Suitable for studs, riding schools and stables        | •                            |
| Suitable for universities, nurseries, and schools     | •                            |
| Suitable for hospitals                                | •                            |
| Suitable for sports clubs                             | •                            |
| Suitable for beauty salons, spas, and fitness centres | •                            |
| Suitable for doctors' and dentists' practices         | •                            |
| Suitable for the petrochemicals industry              | •                            |
| Suitable for the food-processing industry             | •                            |
| Suitable for amusement parks & holiday complexes      | •                            |
| Suitable for state/community care facilities          | •                            |
| Performance data                                      |                              |
| Maximum evaporation capacity in l/hour                | 12.60                        |
| Specific energy consumption in kWh/kg                 | 0.21                         |
| Programme duration in min.                            | 42                           |
| Service life in drying cycles                         | 40000                        |
| Control system  |                              |
| Control system  | M Touch Pro                  |
| Programmability                                       | programmable                 |
| User interface  | Residual moisture controlled |
| Max. delay start in h                                 | 24                           |
| Time left display                                     | •                            |
| Programme sequence indicator                          | •                            |
| Selectable display languages                          | •                            |
| Standard electrical connection                        |                              |
| Heating type  | Heat pump with CleanStream   |
| Electrical connection                                 | 3N AC 400V 50HZ              |

## PDR 922 HP [EL APDR 902]

Professional heat-pump dryer incl. powerful heat pump APDR 902

lowest energy consumption, without complicated exhaust ducting installation.



EAN: 4002516409311 / Material number: 11718440 / Old Material Number: 52922021EU

|  |                    |
|--|--------------------|
| Electric heater rating in kW                                 | 0.00               |
| Heater rating, heat pump in kW                               | 16.00              |
| Total connected load in kW                                   | 6.00               |
| Fuse rating in A   | 16                 |
| <b>Dimensions and weight of dryer</b>                        |                    |
| External dimensions, height in mm                            | 1400               |
| External dimensions, width in mm                             | 906                |
| External dimensions, depth in mm                             | 1164               |
| External dimensions, gross height in mm                      | 1526               |
| External dimensions, gross width in mm                       | 1090               |
| External dimensions, gross depth in mm                       | 1254               |
| Net weight in kg   | 180.2              |
| Gross weight in kg   | 195                |
| Maximum floor load in N/m <sup>2</sup>                       | 2092               |
| <b>Dimensions/weight of HP mod.</b>                          |                    |
| External dimensions, net height in mm                        | 1370               |
| External dimensions, net width in mm                         | 906                |
| External dimensions, net depth in mm                         | 426                |
| External dimensions, gross height in mm                      | 1530               |
| Net weight in kg   | 184.4              |
| External dimensions, gross width in mm                       | 1000               |
| External dimensions, gross depth in mm                       | 800                |
| Gross weight in kg   | 217.0              |
| Maximum floor load in N/m <sup>2</sup>                       | 1809               |
| <b>Emissions data</b>  |                    |
| Emission sound pressure level in the workplace               | 53 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h                       | 4.70               |
| <b>Features</b>  |                    |
| CleanStream (heat exchanger cleaning)                        | •                  |
| Intelligent drum reversal                                    | •                  |
| Axial airflow  | •                  |
| Large-surface fluff filter                                   | •                  |
| PerfectDry   | •                  |
| SoftLift drum ribs   | •                  |
| Communication slot   | •                  |
| Emergency switch-off   | •                  |
| Machine-independent accessories                              | •                  |
| <b>Efficiency and sustainability</b>                         |                    |
| Coolant  | R450a              |
| Refrigerant global warming potential in kg CO <sub>2</sub> e | 605                |
| Appliance global warming potential in kg CO <sub>2</sub> e   | 2299               |
| <b>Connection options</b>                                    |                    |
| Payment system (optional)                                    | •                  |
| Optical interface for service access                         | •                  |
| Peak load cut-out/energy management (optional)               | •                  |
| WiFi tumble dryer  | •                  |
| Connector Box  | •                  |
| LAN module (optional)  | •                  |
| <b>Capacities</b>  |                    |
| Respirator masks [number]                                    | 16                 |
| Overalls [number]  | 3                  |

PDR 922 HP [EL APDR 902]

Professional heat-pump dryer incl. powerful heat pump APDR 902

lowest energy consumption, without complicated exhaust ducting installation.



EAN: 4002516409311 / Material number: 11718440 / Old Material Number: 52922021EU

|   |     |
|---|-----|
| Over jackets [number]                           | 5   |
| Synthetic duvets [number]                       | 2   |
| Synthetic pillows [number]                      | 3   |
| Down duvets [number]                            | 2   |
| Down pillows [number]                           | 4   |
| Cloths, 22 g [number]                           | 364 |
| Cotton mops, 40 cm [number]                     | 84  |
| Cotton mops, 50 cm [number]                     | 73  |
| Microfibre mops, 40 cm [number]                 | 133 |
| Microfibre mops, 50 cm [number]                 | 94  |
| Summer horse blankets [number]                  | 3   |
| <b>Standards, test certificates and symbols</b> |     |
| CE  | •   |
| VDE   | •   |
| VDE-EMC   | •   |
| Splash-proof safety rating IPX4                 | •   |
| WEEE  | •   |
| UKCA  | •   |
| Complies with Machinery Directive 2006/42/EC    | •   |