Miele

PWM 511 [EL DP DD]

Professional washing machine, electric heating, drain pump and detergent drawer, M Touch Pro.



- Drum volume 100 I, load size 11.0 kg
- 14 % less water consumption and 50 % less energy consumption*
- Maximum user convenience with colour touch display M Touch Pro
- Perfect spinning results residual moisture 50 %**, g-factor370
- Connected for the future using LAN and WiFi

EAN: 4002516519966 / Material number: 11961020 / Old Material Number: 51511005GB

Construction type and version	
Construction type	Front loader
Range	Performance
Front	•
Control panel colour	Iron grey Stainless steel
Maximum load with a load ratio of 1:9 in kg	11.0
	·
Load ratio	1:9
Load in kg	11.0
Drum volume in I	100
Door opening [Ø] in mm	370
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	·
Maintenance-free synchronous motor	<u>•</u>
Honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/ kg	7.10
Specific energy consumption for cold water connection in kWh/kg	0.12
Specific water consumption for hot water connection in I/kg	6.90
Specific energy consumption for hot water connection in kWh/kg	0.03
Water consumption with cold water connection in I	78.4
Energy consumption with cold water connection in kW	1.37
Programme duration in minutes with cold water connection	57
Water consumption with hot water connection in I	75.7
Energy consumption with hot water connection in kW	0.32
Programme duration in minutes with cold water and hot water connection	52
Water consumption in ECO programme with cold water connection in I	67.8
Energy consumption in ECO programme with cold water	0.87
Programme duration in minutes with cold water connection in ECO programme	34

Based on the Coloured items 60 °C programme with a warm water connection, compared to predecessor.

[&]quot;Residual moisture specification relates to a hot rinse during the last rinse cycle.



PWM 511 [EL DP DD]

Professional washing machine, electric heating, drain pump and detergent drawer, M Touch Pro.



EAN: 4002516519966 / Material number: 11961020 / Old Material Number: 51511005GB

Water consumption in ECO programme with hot water connection in I	68.3
Energy consumption in ECO programme with hot water	0.13
Programme duration in minutes with cold water and hot	33
water connection in ECO programme	
Residual moisture with cold rinse in %	54
Residual moisture with hot rinse in %	50
Spin speed in rpm	1100
g factor	370
Tested operating hours	30000
Control system	
Control system	M Touch Pro
Programmability	programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for launderettes	•
Programmes for residential homes and apartments	•
Programmes for dry cleaners	•
Programmes for commercial laundries	•
Programmes for small businesses	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Programmes for universities, nurseries, and school	•
Programmes for hospitals	•
Programmes for fast food restaurants	•
Programmes for camp sites	•
Programmes for sports clubs	•
Programmes for beauty clinics, spas, and fitness studios	•
Programmes for domestic use	•
Programmes for doctors' and dentists' practices	•
Dispensing	
Detergent drawer	3 compartments
Flexible dispensing adapter (optional)	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•
Standard electrical connection	
Heating type	Electric
Electrical connection	1N AC 230V 50HZ
Heater rating in kW	5.30
Total connected load in kW	5.50
Fuse rating in A	25
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union



PWM 511 [EL DP DD]
Professional washing machine, electric heating, drain pump and detergent drawer, M Touch Pro.