Miele

PW 6243 [EL WEK]

Hygiene washing machine, electrically heated

Barrier machine for retirement and care homes as well as hospitals.



- Drum volume 240 I, load size 24.0 kg
- Wide variety of programmes special disinfection programme
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 46 %*, g-factor360

EAN: 4002516446996 / Material number: 11812870 / Old Material Number: 51624305ZER

Construction type and version	
Construction type	Hygiene washing machine
Range	Professional
Front	Iron grey
Load ratio	1:10
Load in kg	24.0
Drum volume in I	240
Door opening [W] in mm clean side	352
Door opening [H] in mm clean side	593
Door opening [W] in mm unclean side	352
Door opening [H] in mm unclean side	593
Door opening angle in degrees	153
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
	_
Suitable for hospitals Performance data	•
Tested virucidal efficacy	•
Proven hygiene	10.00
Specific water consumption for hot water connection in I/kg	10.63
Specific energy consumption for hot water connection in kWh/kg	0.09
Programme duration in minutes with cold water connection	68
Programme duration in minutes with cold water and hot water connection	53
Residual moisture with cold rinse in %	50
Residual moisture with hot rinse in %	46
Spin speed in rpm	975
g factor	360
Tested operating hours	30000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
	•
Basic programmes	<u>. </u>
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
Programmes for small businesses	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•

^{*} Residual moisture specification relates to a hot rinse during the last rinse cycle.



PW 6243 [EL WEK]

Hygiene washing machine, electrically heated Barrier machine for retirement and care homes as well as hospitals.



EAN: 4002516446996 / Material number: 11812870 / Old Material Number: 51624305ZER

Programmes for beauty clinics, spas, and fitness studios Dispensing Detergent drawer Liquid dispensing module (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Programmes for beauty clinics, spas, and fitness studios • 4 compartments 12 • • Standard electrical connection Blectric Electric Electric Electric 24.00 Total connected load in kW 50 Water rating in A Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70
Detergent drawer 4 compartments Liquid dispensing module (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electric Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A 50 Water connection/drainage Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Liquid dispensing module (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A Water connection/drainage Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor ◆ Standard electrical connection Electric Heating type Electric Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A 50 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
pumps [number] Empty sensor Standard electrical connection Heating type Electric Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A Water connection/drainage Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Empty sensor Standard electrical connection Heating type Electric Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A 50 Water connection/drainage Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Standard electrical connection Heating type Electric Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A 50 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Heating type Electric Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A 50 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Electrical connection 3N AC 400V 50/60HZ Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A 50 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Heater rating in kW 24.00 Total connected load in kW 25.00 Fuse rating in A 50 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Total connected load in kW 25.00 Fuse rating in A 50 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Fuse rating in A Water connection/drainage Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Water connection/drainage Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union
Hot water [number] union 1x 1/2" hose w/ 3/4" th. union
union
Dump valve DN 70
Dimensions and weight
External dimensions, height in mm 1718
External dimensions, width in mm 1384
External dimensions, depth in mm 1070
External dimensions, gross height in mm 1800
External dimensions, gross width in mm 1570
External dimensions, gross depth in mm 1138
Net weight in kg 820.0
Gross weight in kg 838
Maximum floor load in N/m ² 9808
Emissions data
Emission sound pressure level in the workplace 71 dB(A) re $20 \mu\text{Pa}$
Heat dissipation into the room in MJ/h 9.00
Features
Patented pre-spin •
Cloth reprocessing •
Imbalance monitoring •
Temperature monitoring •
Two indicator lights on the clean side •
Automatic drum positioning and locking •
Special heater element •
Automatic load control+
Volumetric flow meter (optional) •
Communication slot •
Emergency switch-off •
Machine-independent accessories •
Efficiency and sustainability
Recycling rate in % 95
Connection options
Optical interface for service access
Serial interface module RS 232 (optional)



PW 6243 [EL WEK] Hygiene washing machine, electrically heated Barrier machine for retirement and care homes as well as hospitals.



EAN: 4002516446996 / Material number: 11812870 / Old Material Number: 51624305ZER

Peak-load negotiation / energy management (optional)	•
Operating data acquisition	•
Water recovery (optional)	•
Capacities	
Synthetic duvets [number]	3
Synthetic pillows [number]	6
Down duvets [number]	3
Down pillows [number]	6
Cotton mops, 40 cm / 190 g [number]	126
Cotton mops, 50 cm / 220 g [number]	109
Microfibre mops, 40 cm / 120 g [number]	200
Microfibre mops, 50 cm / 170 g [number]	141
Standards, test certificates and symbols	
CE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
UKCA	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•