

PWM 907 [EL DP] / LW

51907151GB / 11106470 / Great Britain

Construction type and design

Line Professional washing machine / Performance Plus
 Construction type / heating Frontloader, stackable / Electric (EL)
 Compliant with EU Machinery Directive Yes

Front Lotus white, enamelled (LW)
 Side panels Lotus white, powder-coated
 Rear panel Galvanised
 Machine lid properties Stainless steel
 Outer drum material Stainless steel

Load capacity 7 kg
 Drum volume 64 l

Drum type Honeycomb drum, perforated rear panel
 Inner drum material Stainless steel
 Door opening [Ø] 300 mm
 Door hinge side Right
 Door opening angle 167 °

Performance data - Water consumption

Specific Coloureds 60°C (CW) 7.00 l/kg
 Coloureds 60°C (CW) 49.0 l
 Mop Standard 60°C (CW)

Specific Coloureds 60°C (HW) 6.60 l/kg
 Coloureds 60°C (HW) 46.0 l
 Mop Standard 60°C (HW)

Performance data - Energy consumption

Specific Coloureds 60°C (CW) 0.14 kWh/kg
 Coloureds 60°C (CW) 0.98 kWh
 Mop Standard 60°C (CW)

Specific Coloureds 60°C (HW) 0.06 kWh/kg
 Coloureds 60°C (HW) 0.44 kWh
 Mop Standard 60°C (HW)

Performance data - Cycle time

Coloureds 60°C (CW) 59 mins.
 Mop Standard 60°C (CW)

Coloureds 60°C (HW) 49 mins.
 Mop Standard 60°C (HW)

Residual moisture - Cold rinse 48 %
 Residual moisture - Hot rinse 45 %
 Residual moisture - Mops

Spin speed 1600 rpm
 g-factor - Spin 704
 Operating hours (tested) 30,000 h

PWM 907 [EL DP] / LW

51907151GB / 11106470 / Great Britain

Controls

Controls M Touch Flex

Standard electrical connection

Heating Electric (EL)

Electrical connection 2N~ 400V 50HZ
Heater rating 5.3 kW
Total rated load 5.5 kW
Fuse rating 13 A

Voltage version 1

Electrical connection 230V~
Heater rating 2.65 kW
Total rated load 2.85 kW
Fuse rating 13 A

Voltage version 2

Electrical connection
Heater rating
Total rated load
Fuse rating

Water connection/drainage

Cold water: 1x 1/2" with 3/4" threaded union
Hot water 1x 1/2" with 3/4" threaded union
Water inlet hose - Length 1.55 m
Drain Drain pump (DP) / Drain hose DN22

Dimensions and weight

Net Height – Width – Depth 850 mm - 596 mm - 714 mm
Net weight 101 kg
Max. floor load in operation 5400 N

Gross Height – Width – Depth 940 mm - 660 mm - 768 mm
Gross weight 105.4 kg

Emissions data

Workplace sound emissions (sound pressure) <70 dB(A) re 20 µPa
Heat dissipation to installation site 1.00 Mj/h

Efficiency and sustainability

Recycling rate 95 %