

PWM 908 [EL DV] / LW

51908254GB / 11390320 / Great Britain

Construction type and design

Line	Professional washing machine / Performance Plus
Construction type / heating	Frontloader, stackable / Electric (EL)
Compliant with EU Machinery Directive	Yes
Front	Lotus white, enamelled (LW)
Side panels	Lotus white, powder-coated
Rear panel	Galvanised
Machine lid properties	Stainless steel
Outer drum material	Stainless steel
Load capacity	8 kg
Drum volume	73 l
Drum type	Honeycomb drum, perforated rear panel
Inner drum material	Stainless steel
Door opening [Ø]	300 mm
Door hinge side	Right
Door opening angle	167 °

Performance data - Water consumption

Specific Coloureds 60°C (CW)	6.40 l/kg
Coloureds 60°C (CW)	51.0 l
Mop Standard 60°C (CW)	
Specific Coloureds 60°C (HW)	6.00 l/kg
Coloureds 60°C (HW)	48.0 l
Mop Standard 60°C (HW)	

Performance data - Energy consumption

Specific Coloureds 60°C (CW)	0.13 kWh/kg
Coloureds 60°C (CW)	1.05 kWh
Mop Standard 60°C (CW)	
Specific Coloureds 60°C (HW)	0.06 kWh/kg
Coloureds 60°C (HW)	0.50 kWh
Mop Standard 60°C (HW)	

Performance data - Cycle time

Coloureds 60°C (CW)	59 mins.
Mop Standard 60°C (CW)	
Coloureds 60°C (HW)	49 mins.
Mop Standard 60°C (HW)	

Residual moisture - Cold rinse	48 %
Residual moisture - Hot rinse	45 %
Residual moisture - Mops	

Spin speed	1600 rpm
g-factor - Spin	704
Operating hours (tested)	30,000 h

PWM 908 [EL DV] / LW

51908254GB / 11390320 / Great Britain

Controls

Controls M Touch Flex

Standard electrical connection

Heating Electric (EL)

Electrical connection ~230V 50HZ

Heater rating 5.3 kW

Total rated load 5.5 kW

Fuse rating 25 A

Voltage version 1

Electrical connection

Heater rating

Total rated load

Fuse rating

Voltage version 2

Electrical connection

Heater rating

Total rated load

Fuse rating

Water connection/drainage

Cold water: 1x 1/2" with 3/4" threaded union

Hot water 1x 1/2" with 3/4" threaded union

Water inlet hose - Length 1.55 m

Drain Drain valve (DV) / Drain connection DN70

Dimensions and weight

Net Height – Width – Depth 850 mm - 596 mm - 714 mm

Net weight 103 kg

Max. floor load in operation 5400 N

Gross Height – Width – Depth 940 mm - 660 mm - 768 mm

Gross weight 107.4 kg

Emissions data

Workplace sound emissions (sound pressure) <70 dB(A) re 20 µPa

Heat dissipation to installation site 1.00 Mj/h

Efficiency and sustainability

Recycling rate 95 %